

Models	RS0608HD/AS1932HD RS0608HD-Li/AS1932HD-Li	
Dimensions		
Max. Working Height	7.8m	25ft7in
A Max. Platform Height	5.8m	19ft
B Min. Platform Height	1.05m	3ft5in
C Platform Length	1.7m	5ft7in
D Platform Extension Distance	0.9m	2ft11in
E Platform Width	0.76m	2ft6in
Guardrail Height	1.1m	3ft7in
F Overall Height:		
Wth Guardrail Raised	2.18m	7ft2in
With Guardrail Folded	1.79m	5ft10in
G Overall Length	1.86m	6ft1in
H Overall Width	0.83m	2ft9in
I Wheelbase	1.38m	4ft6in
J Pit Guard Plate Lowered	0.02m	0.79in
K Ground Clearance - Center	0.07m	2.76in
Performance		
Max. Number of Workers	2 Persons(indoor) 1 Perspon(outdoor)	
Platform Capacity	230kg	507lbs
Safe Working Load of Extended Platform	113kg	249lbs
Travel Speed - Stowed	3.2km/h	2.0mph
Travel Speed - Raised	0.8km/h	0.5mph
Gradeability - Stowed	25% (14°)	
Turning Radius - Inside	0	
Turning Radius - Outside	1.67m	5ft6in
Max. Allowable Inclination (Lateral/ Vertical)	1.5°/3°	
Lift/ Lower Time	21s/25s	
Control System	Proportional	
Drive System	Dual Front Wheel	
Multi-disc Brakes	Dual Rear Wheel	
Solid Non-Marking Tires (outer diameter × width)	323mm X100mm	12in X 4in
Power		
Battery	24V	
Battery (Lead-acid)	4x12V 160AH	
Battery (Lithium-ion batteries)	25.6V 135Ah Li-ion	
Overall Weight	1620kg	3571lbs

