

Models	RS0808AC/AS2632AC RS0808AC-Li/AS2632AC-Li	
Dimensions		
Max. Working Height	10m/8m (in/out)	32ft10in/26ft3in (in/out)
A Max. Platform Height	8m/6m (in/out)	26ft3in/19ft8in (in/out)
B Min. Platform Height	1.25m	4ft1in
C Platform Length	2.27m	7ft5in
D Platform Extension Distance	0.9m	2ft11in
E Platform Width	0.81m	2ft8in
Guardrail Height	1.1m	3ft7in
F Overall Height: Wth Guardrail Raised	2.36m	7ft9in
With Guardrail Folded	1.86m	6ft1in
G Overall Length	2.47m	8ft1in
H Overall Width	0.83m	2ft9in
I Wheelbase	1.87m	6ft2in
J Pit Guard Plate Lowered	0.02m	0.79in
K Ground Clearance - Center	0.11m	4.33in
Performance		
Max. Number of Workers	2 Persons(indoor) 1 Perspon(outdoor)	
Platform Capacity	230kg	507lbs
Safe Working Load of Extended Platform	113kg	249lbs
Travel Speed - Stowed	4.0km/h	2.5mph
Travel Speed - Raised	0.8km/h	0.5mph
Gradeability - Stowed	25% (14°)	
Turning Radius - Inside	0	
Turning Radius - Outside	2.1m	6ft11in
Max. Allowable Inclination (Lateral/ Vertical)	1.5°/3°	
Lift/ Lower Time	35s/36s	
Control System	Proportional	
Drive System	Dual Front Wheel	
Multi-disc Brakes	Dual Front Wheel	
Solid Non-Marking Tires (outer diameter × width)	381mm X127mm	15in X 5in
Power		
Lifting Motor	24V/4.5KW	
Drive Motor	2x16V/0.7KW	
Battery (Lead-acid)	4x6V 220AH	
Battery (Lithium-ion batteries)	25.6V 230Ah Li-ion	
Overall Weight	2240kg	4938lbs

